

INFORMATIONAL PROPOSAL (For information only, not to be used for bidding)

NEBRASKA DEPARTMENT OF ROADS
LETTING DATE : November 13, 2003

CALL ORDER: N25 CONTRACT ID: 5254

CONTROL NO./SEQ. NO.: 51254 /000 PROJECT NO.: STR-80-1(1025)

TENTATIVE START DATE: 07/12/04 CONTRACT TIME: 50 WORKING DAYS

LOCATION: I-80, BUSHNELL - KIMBALL

IN COUNTY: KIMBALL

BIDDER

GROUP 6 BRIDGE AT STA. 277+59.45 LT.
GROUP 6A BRIDGE AT STA. 277+59.45 RT.
GROUP 6B BRIDGE AT STA. 341+74.30 LT.
GROUP 6C BRIDGE AT STA. 341+74.30 RT.
GROUP 6D BRIDGE AT STA. 1093+23.57 LT.
GROUP 6E BRIDGE AT STA. 1093+23.57 RT.
GROUP 10 GENERAL ITEMS

SEE SPECIAL PROVISIONS FOR GROUP TIES

NOTES

THE TOTAL AMOUNT OF WORK WHICH WILL BE ACCEPTED IN THIS LETTING IS LIMITED TO \$_____.

THE NUMBER OF _____ CONTRACTS WHICH WILL BE ACCEPTED IN THIS LETTING IS LIMITED TO _____.

THIS PROJECT (IS TIED)(IS NOT TIED) TO PROJECT NO. STR-80-2(1014)

STRIKE OUT WORDS IN PARENTHESIS THAT DO NOT APPLY.

NOTICE TO ALL BIDDERS

To report bid rigging activities, call: 1-800-424-9071

The U.S. Department of Transportation (DOT) operates the above toll-free "hotline" Monday through Friday, 8:00 a.m. to 5:00 p.m. eastern time. Anyone with knowledge of possible bid rigging, bidder collusion, or other fraudulent activities should use the "hotline" to report such activities.

The "hotline" is part of the DOT's continuing effort to identify and investigate highway construction contract fraud and abuse and is operated under the direction of the DOT Inspector General. All information will be treated confidentially and caller anonymity will be respected.

LETTING QUESTIONS

Prior to the letting, any questions pertaining to the Special Provisions or the plans for this project should be directed to Construction Division personnel at (402) 479-4568 or (402) 479-4529.

STATE OF NEBRASKA
DEPARTMENT OF ROADS

Required Provisions Supplemental to the
Standard Specifications for Highway Construction

I. Application

These contract provisions shall apply to all work performed on the contract by the contractor with his own organization and with the assistance of workmen under his immediate superintendence and to all work performed on the contract by piecework, station work, or by subcontract.

The contractor shall insert in each of his subcontracts all of the stipulations contained in the Special Provisions and these Required Provisions.

A breach of any of the stipulations contained in these Required Provisions may be grounds for termination of the contract.

II. Equal Opportunity

1. **Selection of Labor**

During the performance of this contract, the contractor shall not discriminate against labor from any other state.

2. **Nebraska Fair Employment Practices Act**

The contractor shall not discriminate against any employee or applicant for employment, to be employed in the performance of this contract with respect to his hire, tenure, terms, conditions, or privileges of employment, because of his race, color, religion, sex or national origin. The contractor agrees to post in a conspicuous place or places a notice to be provided by the State Highway Department which sets forth excerpts of the Act.

3. **Nebraska Equal Pay Act**

The contractor shall not discriminate on the basis of sex by paying wages to employees of one sex at a lesser rate than the rate paid to employees of the opposite sex for comparable work on jobs which have comparable requirements. An abstract of the Act is included on the notice which is provided by the State Highway Department.

April 4, 1995

III. Employment of Labor

1. **General**

No person under the age of sixteen (16) years, and no one whose age or physical condition is such as to make his employment dangerous to his health or safety, or to the health and safety of others shall be employed on any project. This paragraph shall not be construed to deny the employment of older people or physically handicapped persons, otherwise employable, where such persons may be safely assigned to work which they can ably perform.

No person currently serving sentence to a penal or correction institution shall be employed on any project.

Except as specifically provided under this section, workers who are qualified by training or experience to be assigned to projects of this character shall not be discriminated against on any grounds whatsoever.

2. **Payrolls**

Payrolls and basic records relating thereto will be maintained during the course of the work and preserved for a period of three years thereafter for all laborers and mechanics working on the site of the work.

The contractor's and subcontractor's payroll records shall be available for inspection by authorized representatives of the State Highway Department and authorized representatives of Federal Agencies.

The wages of labor shall be paid in legal tender of the United States, except that this condition will be considered satisfied if payment is made by a negotiable check, on a solvent bank, which may be cashed readily by the employee in the local community for the full amount, without discount or collection charges of any kind. Where checks are used for payment the contractor shall make all necessary arrangements for them to be cashed and shall give information regarding such arrangements.

No fee of any kind shall be asked or accepted by the contractor or any of his agents from any person as a condition of employment on the project.

No laborers shall be charged for any tools used in performing their respective duties except for reasonably avoidable loss or damage thereto.

Every employee on the work covered by this contract shall be permitted to lodge, board and trade where and with whom he elects and neither the contractor nor his agents, nor his employees shall directly or indirectly require as a condition of employment that an employee shall lodge, board or trade at a particular place or with a particular person.

No charge shall be made for any transportation furnished by the contractor or his agents to any person employed on the work.

April 4, 1995

No individual shall be employed as a laborer on this contract except on a wage basis, but this shall not be construed to prohibit the rental of teams, trucks or other equipment from individuals. No such rental agreement, or any charges for feed, gasoline, supplies, or repairs on account of such agreement, shall cause any deduction from the wages accruing to any employee except as authorized by the regulations hereinbefore cited.

IV. Safety and Accident Prevention

In the performance of this contract, the contractor shall comply with all applicable Federal, State and local laws governing safety, health and sanitation. The contractor shall provide all safeguards, safety devices and protective equipment and take any other needed actions, on his own responsibility or as the contracting officer may determine, reasonably necessary to protect the life and health of employees on the job and the safety of the public and to protect property in connection with the performance of the work covered by the contract.

V. Subletting or Assigning the Contract

The contractor shall perform with his own organization contract work amounting to not less than 30 percent of the total contract amount except that any items designated in the contract as "Specialty Items" may be performed by subcontract and the amount of any such "Specialty Items" so performed may be deducted from the total contract amount before computing the amount of work required to be performed by the contractor with his own organization.

Any items that have been selected as "Specialty Items" for the contract are listed as such in the Special Provisions found elsewhere in the contract.

No portion of the contract shall be sublet, assigned, or otherwise disposed of except with the written consent of the contracting officer or his authorized representative. Requests for permission to sublet assign or otherwise dispose of any portion of the contract shall be in writing and accompanied by a showing that the organization which will perform the work is particularly experienced and equipped for such work. The contractor shall give assurance that the minimum wage for labor as stated in his proposal shall apply to labor performed on all work sublet, assigned or otherwise disposed of in any way. Consent to sublet, assign or otherwise dispose of any portion of the contract shall not be construed to relieve the contractor of any responsibility for the fulfillment of the contract.

April 4, 1995

**SPECIAL PROVISIONS
FOR
STATE
PROJECT NO. STR-80-1(1025)
GENERAL CONDITIONS**

Sealed bids for the work contemplated in this proposal form will be received at the office of the Nebraska Department of Roads in Room 104 of the Central Office Building at 1500 Highway 2 at Lincoln, Nebraska, on November 13, 2003, until 1:30 P.M.

Bids submitted by mail should be addressed to the Nebraska Department of Roads, c/o Contract Lettings Section, P.O. Box 94759, Lincoln, NE 68509-4759.

The 1997 English Edition of the Standard Specifications for Highway Construction, including all amendments and additions thereto effective at the date of the contract, are made a part of these Special Provisions, through reference.

The Supplemental Specifications to the 1997 English Edition of the Standard Specifications for Highway Construction dated July 12, 2001, including all amendments and additions thereto effective at the date of the contract, are made part of these Special Provisions, through reference.

The Required Provisions dated April 4, 1995, are attached to and are a part of this proposal form.

The attention of bidders is directed to the Required Provisions covering subletting or assigning the contract.

The proposal contains a statement that the contractor is complying with, and will continue to comply with, fair labor standards in the pursuit of his business and in the execution of the work contemplated in this proposal.

Fair labor standards shall be construed to mean such a scale of wages and conditions of employment as are paid and maintained by at least fifty per cent of the contractors in the same business or field of endeavor as the contractor filing this proposal.

GROUPS 6, 6A, 6B, 6C, 6D, 6E AND 10 ARE TIED TOGETHER AND BIDDING PROPOSAL FORMS FOR THIS WORK WILL BE ISSUED AND A CONTRACT AWARDED TO A CONTRACTOR WHO IS QUALIFIED FOR BRIDGE.

STATUS OF UTILITIES

No utilities have been or will be required to relocate within the limits of this project.

Underground utilities may exist within the limits of this project. The Contractor shall determine to his satisfaction the extent of occupancy of any underground utilities located within the respective construction areas and the extent of conflict with the proposed work under this contract.

Any utility adjustments or interruption of service for the convenience of the Contractor shall be the sole responsibility of the Contractor.

To arrange for utilities to locate and flag their underground facilities, contact The Diggers Hotline of Nebraska at 1-800-331-5666.

**STATUS OF RIGHT-OF-WAY
(S1-16-0801)**

According to the best information available, all necessary right-of-way has been acquired.

**REQUIRED SUBCONTRACTOR/SUPPLIER QUOTATIONS LIST
(S1-43-0603)**

At bid submittal, all bidders must provide to the NDOR the identity of all firms who provided quotations on all projects, including both DBEs and non-DBEs. This information must be on a form provided by the NDOR Contracts Office.

If no quotations were received, the bidder must indicate this in the space provided.

Each bidder will be required to submit one list per letting to cover all projects bid.

**CONTROL OF WORK
(S1-43-0901)**

Subsection 105.08 in the 1997 Standard Specifications is void and replaced by the following:

105.08 - Authority and Duty of the Inspector

Department inspectors are authorized to inspect all work performed and all materials furnished. Such inspection may extend to the preparation, fabrication, or manufacture of the materials. The inspector has the authority to reject work or materials until any issues can be decided, including the right to suspend work. The inspector is not authorized to alter or waive the provisions of the contract or act as a supervisor for the Contractor.

105.13 – Tentative Acceptance of Portions of the Project

Paragraph 3.a. of Subsection 105.13 is amended by deleting the word “normal”.

**LEGAL RELATIONS AND RESPONSIBILITY TO THE PUBLIC
(S1-43-1001)**

107.14 – Opening of Sections of the Project to Traffic

Subsection 107.14 Paragraphs 2.b.(1) and (2) are void and replaced by the following:

- 2.b. (1) Whenever the Department permits the public use of a highway undergoing construction, repair, or maintenance in lieu of a detour route, the Contractor shall not be held responsible for damages to those portions of the project upon which the Department permitted public use, when such damages are the result of no proximate act or failure to act on the part of the Contractor.

- (2) If the traveling public should cause damage to the roadway, the Contractor shall assist the State in identifying the responsible party and the Contractor shall as a minimum if present at the time of the damage record pertinent information regarding the accident. (Who caused the damage; when the damage occurred; and how the damage occurred.)

107.15 – Contractor’s Responsibility for Work

Subsection 107.15 is amended by adding Paragraph 1.b.(3) as follows:

- (3) The Contractor shall not be held responsible for damage caused by the traveling public on those portions of the project where the Department has permitted public use of the road in lieu of using a detour route and the damage as not the result of any proximate act or failure to act on the part of the Contractor.

MEASUREMENT AND PAYMENT (S1-43-0901)

109.08 – Acceptance, Final Payment, and Termination of Contractor’s Responsibility

Subsection 109.08 Paragraph c. amended by deleting the word “normal”.

Subsection 109.08 Paragraph d. is void and replaced by the following:

- d. If the traveling public should cause damage to the roadway the Contractor shall assist the State in identifying the responsible party and the Contractor shall as a minimum if present at the time of the damage record pertinent information regarding the accident. (Who caused the damage; when the damage occurred; and how the damage occurred.)

LIABILITY INSURANCE (S1-43-1103)

Paragraph 2.a. of Subsection 107.13 in the Standard Specifications is void and superseded by the following:

- a. The General Liability coverage for bodily injury liability shall be not less than \$1,000,000 for injuries, including accidental death, in any one occurrence, and subject to an aggregate limit of not less than \$2,000,000.

Paragraph 2.b. of Subsection 107.13 is void and superseded by the following:

- b. The amount of property damage liability insurance shall be not less than \$1,000,000.

**SPECIAL PROSECUTION AND PROGRESS
(Migratory Birds)**

Paragraph 4.h. of Subsection 107.01 in the Standard Specifications for Highway Construction is void.

CONSTRUCTION DETAILS

**TEMPORARY TRAFFIC CONTROL DEVICES
(S4-9-1201)**

Paragraphs 2.a. of Subsection 422.05 in the Standard Specifications is void and superseded by the following:

2.a. If signs are not returned or are returned damaged, and the damage is beyond reasonable "wear and tear" and the damage was caused by the Contractor, then the Contractor shall be charged the value of the missing or damaged items. These charges shall be deducted from monies due the Contractor upon final payment.

**TYPE B HIGH INTENSITY WARNING LIGHTS
(S4-9-1002)**

All references in the plans to Type B High Intensity Warning Lights shall be considered void. The plans will not be revised to reflect this change.

TEMPORARY PAVEMENT MARKING

Section 1069 in the Standard Specifications is amended to include the following:

Prior to the initial placement of the markings, temporary paint, Type II tape or raised pavement markers, the pavement upon which the markings are to be placed shall be dry, cleaned and properly prepared by shot blasting, as a minimum, and to the extent recommended by the manufacturer so that all contaminants, loose debris, and other foreign material are completely removed. Surface preparation for any subsequent application shall consist of air blasting and brushing the roadway surface to remove all loose dirt, mud or other debris and to dry the surface. Each additional application of paint shall be applied over the previously painted stripes.

Initial surface preparation requiring shot blasting shall be paid at the contract unit price per linear foot for the item "Temporary Pavement Marking Surface Preparation". Surface preparation for repainting, consisting of air blasting and brushing, shall be subsidiary to other items for which payment is made.

RELOCATE INERTIAL BARRIER SYSTEM

Subsection 422.04 and 422.05 in the Supplemental Specifications is amended to include the following item:

Pay Item	Pay Unit
Relocate Inertial Barrier System	Each (Ea)

47B CONCRETE PAVEMENTS AND 47BD CONCRETE FOR BRIDGES (S10-4-0403)

General

Section 1002 in the 1997 Standard Specifications and Supplemental Specifications is amended to include the following:

For the purpose of this Special Provision, Type IPN shall mean Type IP cement made with 15 to 25 percent natural pozzolan and Type IPF shall mean Type IP cement made with 15 to 25 percent Class F fly ash. All cements must conform to the requirements of Section 1004 in the 1997 Standard Specifications and Supplemental Specifications.

47BD Concrete for Bridges and Barriers

The 47BD concrete used in bridge decks, approach slabs, bridge rails, and barriers shall be proportioned using one of the alternates shown in Table I.

TABLE I (ENGLISH)
CLASS 47BD CONCRETE PROPORTIONS

Alt.	Cement Type	Pounds of Cement per Cu.Yd.	Pounds of Class F Fly Ash	Air Content Percent		Pounds of Total Agg. per Cu.Yd.		Ratio of Total Agg. Percent	Type of Coarse Agg.****
				Min.	Max.	Min.	Max.		
1	I or II	590	130 Min.	5.0	7.5	2530	2950	30±3	Limestone
2	IPN	658	0*	5.0	7.5	2530	2950	30±3	Limestone
3	IPF	658	0**	5.0	7.5	2530	2950	30±3	Limestone
4	I or II	658***	0***	5.0	7.5	2530	2950	30±3	Limestone

TABLE I (METRIC)
CLASS 47BD CONCRETE PROPORTIONS

Alt.	Cement Type	Kg of Cement per Cu. Meter	Kg of Class F Fly Ash	Air Content Percent		Kg of Total Agg. per Cu.Meter		Ratio of Total Agg. Percent	Type of Coarse Agg.****
				Min.	Max.	Min.	Max.		
1	I or II	350	77 Min.	5.0	7.5	1500	1750	30±3	Limestone
2	IPN	390	0*	5.0	7.5	1500	1750	30±3	Limestone
3	IPF	390	0**	5.0	7.5	1500	1750	30±3	Limestone
4	I or II	390***	0***	5.0	7.5	1500	1750	30±3	Limestone

* Class C or F fly ash may be substituted in the mix design provided the total pozzolan content does not exceed 25 percent. The mix may be modified by substituting an amount of fly ash equal to the weight of cement removed.

** No additional fly ash substitution is allowed.

*** Total alkali content shall not exceed 3 lbs./yd.³ (1.8 Kg/m³)

**** Alternate Aggregate from an approved source may be substituted for limestone.

Water reducing and set retarding admixtures shall be used in accordance with the manufacturer's recommendations of dosage rates.

47B Concrete Pavements

The 47B concrete used in concrete pavements shall be proportioned using one of the alternates shown in Table II.

TABLE II (ENGLISH)
CLASS 47B CONCRETE PAVEMENT PROPORTIONS

Alt.	Cement Type	Pounds of Cement per Cu.Yd.	Pounds of Class F Fly Ash	Air Content Percent		Pounds of Total Agg. per Cu.Yd.		Ratio of Total Agg. Percent	Type of Coarse Agg.****
				Min.	Max.	Min.	Max.		
1	I or II	510	110 Min.	5.0	7.5	2876	3130	30±3	Limestone
2	IPN	564*	0*	5.0	7.5	2876	3130	30±3	Limestone
3	IPF	564**	0**	5.0	7.5	2876	3130	30±3	Limestone
4	I or II	564***	0***	5.0	7.5	2876	3130	30±3	Limestone

TABLE II (METRIC)
CLASS 47B CONCRETE PAVEMENT PROPORTIONS

Alt.	Cement Type	Kg of Cement per Cu. Meter	Kg of Class F Fly Ash	Air Content Percent		Kg of Total Agg. per Cu.Meter		Ratio of Total Agg. Percent	Type of Coarse Agg.****
				Min.	Max.	Min.	Max.		
1	I or II	303	65 Min.	5.0	7.5	1706	1857	30±3	Limestone
2	IPN	335*	0*	5.0	7.5	1706	1857	30±3	Limestone
3	IPF	335**	0**	5.0	7.5	1706	1857	30±3	Limestone
4	I or II	335***	0***	5.0	7.5	1706	1857	30±3	Limestone

* Class C or F fly ash may be substituted in the mix design provided the total pozzolan content does not exceed 25 percent. The mix may be modified by substituting an amount of fly ash equal to the weight of cement removed.

** No additional fly ash substitution is allowed.

*** Total alkali content shall not exceed 3 lbs./yd.³ (1.8 Kg/m³)

**** Alternate Aggregate from an approved source may be substituted for limestone.

Water reducing admixtures shall be used in accordance with the manufacturer's recommendations of dosage rates.

FLY ASH (S10-5-0801)

Subsection 1008.01 in the Standard Specifications is void and superseded by the following:

Fly ash shall be Class C or F meeting the requirements of ASTM C 618.

**STRUCTURAL STEEL
(S10-5-0801)**

Section 1045 of the Standard Specifications is amended to include the following:

1045.03 -- Steel Plate Substitution

The Contractor may use either English or Metric steel plates in accordance with Table 1045.01.

Table 1045.01			
English-Metric Steel Plate Substitution Table			
Metric (millimeters)	English (inches)	Metric (millimeters)	English (inches)
9	3/8	32	1 1/4
10	3/8	35	1 3/8
11	7/16	38	1 1/2
12	1/2	40	1 5/8
14	9/16	45	1 3/4
16	11/16	50	2
18	3/4	55	2 1/4
20	13/16	60	2 3/8
22	7/8	70	2 3/4
25	1	80	3 1/4
28	1 1/8	90	3 1/2
30	1 1/4		

**REPAIR OF DAMAGED METALLIC COATINGS
(S10-5-0801)**

Paragraph 2. of Subsection 1061.01 in the Standard Specifications is void and superseded by the following:

2. The material used for repair shall provide a minimum coating thickness of at least 50 µm with one application.

**CORRUGATED METAL PIPE
(S10-5-0801)**

Table 1035.01 in Section 1035 of the Supplemental Specifications is amended by deleting the title "Steel and Aluminum Culvert Thickness".

**METAL FLARED-END SECTIONS
(S10-5-0801)**

Table 1036.01 in Section 1036 of the Supplemental Specifications is amended by deleting the title "Steel and Aluminum Flared-End Thickness".

**REINFORCED CONCRETE PIPE, MANHOLE RISERS,
AND FLARED-END SECTIONS
(S10-5-0801)**

Paragraph 3.a. of Subsection 1037.02 in the Supplemental Specifications is void and superseded by the following:

3.a. Round reinforced concrete pipe shall conform to the requirements of AASHTO M 170-95 with the exception of the minimum circumferential reinforcing (in²/ft. (mm²/m) of pipe wall) for 15, 21, and 24 inch (380, 460, 600 mm) Class III pipe, as shown below:

Paragraph 3.b. of Subsection 1037.02 is void and superseded by the following:

b. AASHTO M 170-95 Specifications are modified as follows:

Paragraph 4. of Subsection 1037.02 is void and superseded by the following:

4. Reinforced concrete arch pipe shall conform to the requirements of AASHTO M 206-95.

Paragraph 5. of Subsection 1037.02 is void and superseded by the following:

5. Reinforced concrete elliptical pipe shall conform to the requirements of AASHTO M 207-95.

Paragraph 7. of Subsection 1037.02 is void and superseded by the following:

7. Concrete flared-end sections shall be of the design shown in the plans and in conformance with the applicable requirements of AASHTO M 170-95, Class II pipe, AASHTO M 206-95, Class A-II pipe, or AASHTO M 207-95, Class HE-II pipe for the diameter of pipe which it is to be installed.

**HIGH TENSILE BOLTS, NUTS, AND WASHERS
(S10-5-1001)**

Subsection 1058.02 in the Supplemental Specifications is void.

Paragraph 4.b.(5) in the Standard Specifications is void and superseded by the following:

- (5) The bolt, nut, and washer assembly shall be assembled in a Skidmore-Wilhelm calibrator or an acceptable equivalent device. For bolts that are too short to be assembled in the calibrator, see Subsection 1058.03, Paragraph 4.b.(9).

**ELASTOMERIC BEARINGS AND LAMINATED
BEARING PADS
(S10-5-0903)**

Paragraph 2. of Subsection 1068.02 in the Standard Specifications is void and superseded by the following:

2. Samples and Certification shall be furnished in accordance with NDR's *Materials Sampling Guide*.

Paragraph 3. of Subsection 1068.02 is void.

**STEEL BARS FOR CONCRETE REINFORCEMENT
(S10-5-1201)**

Section 1020 in the Standard Specifications is void and superseded by the following:

1020.01 - Description

Steel tie bars for longitudinal joint reinforcement in concrete pavements shall be epoxy coated and deformed Grade 40 or 60 billet steel as shown in the plans, specifications or Special Provisions.

1020.02 - Material Characteristics

1. Billet-steel bars shall conform to the requirements of ASTM A 615/A 615M.
2. Epoxy coatings shall conform to the requirements in Section 1021 of the Standard Specifications and Supplemental Specifications.

1020.03 - Acceptance Requirements

Acceptance shall be based on sampling, testing, and certification requirements in accordance with the NDR *Materials Sampling Guide*.

**EPOXY COATED REINFORCING STEEL
(S10-5-0403)**

Table 1021.01 in Section 1021 of the Standard Specifications is void and superseded by the following:

Table 1021.01			
Bend Test Requirements			
English		Metric	
Bar No.	Mandrel Diameter (inches)	Bar	Mandrel Diameter (millimeters)
3	3	10	75
4	4	13	100
5	5	16	125
6	6	19	150
7	7	22	175
8	8	25	200
9	9	29	230
10	10	32	250
11	11	36	280
14	17	43	430
18	23	57	580

**PROPOSAL GUARANTY
(S1-38-0801)**

As an evidence of good faith in submitting a proposal for this work or for any portion thereof as provided in the proposal form, the bidder must file with his proposal a bid bond, which must be executed on the Department of Roads' Bid Bond form, in the amount of 5 percent of the amount bid for any group of items or collection of groups for which the bid is submitted. Any alterations, conditions or limitations added to the Department of Roads' Bid Bond form will be unacceptable and cause the bid not to be opened and read.

* * * * *

N25INFNOV03

47B CONCRETE PAVEMENTS AND 47BD CONCRETE FOR BRIDGES..... 10

CONSTRUCTION DETAILS.....9

CONTROL OF WORK.....7

CORRUGATED METAL PIPE..... 14

ELASTOMERIC BEARINGS AND LAMINATED BEARING PADS 15

FLY ASH..... 12

GENERAL CONDITIONS.....6

HIGH TENSILE BOLTS, NUTS, AND WASHERS..... 15

LEGAL RELATIONS AND RESPONSIBILITY TO THE PUBLIC.....7

LIABILITY INSURANCE 8

MEASUREMENT AND PAYMENT8

METAL FLARED-END SECTIONS..... 14

PROPOSAL GUARANTY 16

REINFORCED CONCRETE PIPE, MANHOLE RISERS, AND FLARED-END SECTIONS..... 14

RELOCATE INERTIAL BARRIER SYSTEM 10

REPAIR OF DAMAGED METALLIC COATINGS..... 13

REQUIRED SUBCONTRACTOR/SUPPLIER QUOTATIONS LIST 7

SPECIAL PROSECUTION AND PROGRESS (Migratory Birds).....9

STATUS OF RIGHT-OF-WAY.....7

STATUS OF UTILITIES.....6

STEEL BARS FOR CONCRETE REINFORCEMENT 15

STRUCTURAL STEEL..... 13

TEMPORARY PAVEMENT MARKING.....9

TEMPORARY TRAFFIC CONTROL DEVICES9

TYPE B HIGH INTENSITY WARNING LIGHTS.....9