

Materials Sampling Guide

Table of Contents

Section 2

Asphaltic Materials

1. Asphaltic Oils.....Page 2-1
2. Asphalt, Emulsified Anionic and Cationic..... Page 2-1
3. Performance Graded Binder.....Page 2-2

DATE: 08-23-00
REVISED: 10-02-08

Minimum Material Certificate, Sample and Inspection Requirements							
MATERIAL	TYPE OF TEST	Q.C. SAMPLING AND TESTING BY CONTRACTOR	VERIFICATION SAMPLING AND TESTING BY NDOR			LOCATION OF ADDITIONAL INFORMATION	
SECTION: 2 – Asphaltic Materials			FIELD PERSONNEL	BRANCH LAB	LINCOLN LAB	NOTE No.	PAGE No.
1) Asphaltic Oils	Quality	-----	<p>One quart sample from each tank car or truck load following receipt at project.</p> <p>Sample to be submitted no later than 5 days to the Lincoln Laboratory.</p>	-----	Acceptance samples to be tested in the Lincoln Laboratory	1 2	1 2
2) Asphalt, Emulsified Anionic and Cationic	Quality	-----	<p>One quart sample for every tank car or truck load following receipt at project.</p> <p>Sample to be submitted (In a one quart plastic container) no later than 5 days to the Lincoln laboratory.</p> <p>No field sample is required for shipments from a source that is on the approved products list unless the appearance of the material or any other physical characteristic of it indicates contamination or noncompliance with the specifications.</p>	-----	Acceptance samples to be tested in the Lincoln Laboratory.	1 2	1 2

Minimum Material Certificate, Sample and Inspection Requirements							
MATERIAL	TYPE OF TEST	Q.C. SAMPLING AND TESTING BY CONTRACTOR	VERIFICATION SAMPLING AND TESTING BY NDOR			LOCATION OF ADDITIONAL INFORMATION	
SECTION: 2 – Asphaltic Materials (continued)			FIELD PERSONNEL	BRANCH LAB	LINCOLN LAB	NOTE No.	PAGE No.
3)Performance Graded Binder	Quality	-----	<p>Using two one quart cans submit a two quart sample for each lot (3750 tons) or parts thereof of asphaltic concrete produced. A minimum of three two-quart samples per project.</p> <p>Sample to be submitted no later than 10 days to the Lincoln Laboratory.</p> <p>(This sampling frequency must be followed for each grade and source of PG Binder used on the project).</p> <p>The samples must be accompanied by a DR-12 "Sample Identification Form". The tonnage of asphaltic concrete that the sample represents must be reported.</p> <p>Sample to be submitted to the Lincoln Laboratory.</p>	-----	Acceptance samples to be tested in the Lincoln Laboratory.	1 2	1 2