

Materials Sampling Guide

Table of Contents

Section 6

Gravel and Crushed Rock for Surfacing

1. Gravel for Surfacing..... Page 6-1  
2. Crushed Rock for Surfacing..... Page 6-1

DATE: 08-23-00  
REVISED: 07-12-02

Minimum Material Certificate, Sample and Inspection Requirements							
MATERIAL	TYPE OF TEST	Q.C. SAMPLING AND TESTING BY CONTRACTOR	VERIFICATION SAMPLING AND TESTING BY NDOR			LOCATION OF ADDITIONAL INFORMATION	
Section: 6 – Gravel and Crushed Rock for Surfacing			FIELD PERSONNEL	BRANCH LAB	LINCOLN LAB	NOTE No.	PAGE No.
1) Gravel For Surfacing	Quality & Gradation	-----	<p>See Standard Specifications, Supplemental Specifications and/or the Project Provisions for sampling and testing requirements.</p> <p>Project personnel will provide the 12 and 60 pound samples needed to perform the testing shown under the Lincoln Lab column.</p> <p>The sample shall be taken at the project.</p>	-----	<p>One 60 pound sample for quality tests first 1000 cubic yard if so designated on "Source Of Aggregates To Be Used" form.</p> <p>One 12 pound sample for gradation test each 1,000 cubic yard or fraction thereof (Duplicate of sample tested in the field)</p>	1 4	1 5
2) Crushed Rock for Surfacing	Quality & Gradation	-----	<p>One sample for each 500 cubic yards or fraction thereof, either at the source or on the project. (Certified quarry personnel may obtain and test this sample).</p> <p>Project personnel will provide the 60 pound sample needed to perform the testing shown under the Lincoln Lab column.</p> <p>The sample shall be taken at the project.</p>	-----	<p>No samples required if source is Kerford or Martin Marietta @ Weeping Water or Fort Calhoun @ Fort Calhoun.</p> <p>One 60 pound sample is required for each 2,000 cubic yards or fraction thereof, from all other sources.</p>	1 5	1 6