

Materials Sampling Guide

Table of Contents

Section 6

Gravel and Crushed Rock for Surfacing

1. Gravel for Surfacing..... Page 6-1
2. Crushed Rock for Surfacing..... Page 6-1

DATE: 08-23-00
REVISED: 02-12-04

| Minimum Material Certificate, Sample and Inspection Requirements | | | | | | | |
|--|---------------------|---|--|------------|--|------------------------------------|----------|
| MATERIAL | TYPE OF TEST | Q.C. SAMPLING AND TESTING BY CONTRACTOR | VERIFICATION SAMPLING AND TESTING BY NDOR | | | LOCATION OF ADDITIONAL INFORMATION | |
| Section: 6 – Gravel and Crushed Rock for Surfacing | | | FIELD PERSONNEL | BRANCH LAB | LINCOLN LAB | NOTE No. | PAGE No. |
| 1) Gravel For Surfacing | Quality & Gradation | ----- | <p>See Standard Specifications, Supplemental Specifications and/or the Project Provisions for sampling and testing requirements.</p> <p>Project personnel will provide the 10 and 60 pound samples needed to perform the testing shown under the Lincoln Lab column.</p> <p>The sample shall be taken at the project.</p> | ----- | <p>One 60 pound sample for quality tests first 1000 cubic yard if so designated DR FORM 324 "Source Of Aggregates To Be Used."</p> <p>One 10 pound sample for gradation test each 1,000 cubic yard or fraction thereof (Duplicate of sample tested in the field)</p> | 1 4 | 1 4 |
| 2) Crushed Rock for Surfacing | Quality & Gradation | ----- | <p>One sample for each 750 cubic yards or fraction thereof, either at the source or on the project. (Certified quarry personnel may obtain and test this sample).</p> <p>Project personnel will provide the 60 pound sample needed to perform the testing shown under the Lincoln Lab column.</p> <p>The sample shall be taken at the project.</p> | ----- | <p>No samples required if source is Kerford or Martin Marietta @ Weeping Water or Fort Calhoun @ Fort Calhoun.</p> <p>One 60 pound sample is required for each 3,000 cubic yards or fraction thereof, from all other sources.</p> | 1 5 | 1 4 |