

Materials Sampling Guide

Table of Contents

Section 7

Mineral Aggregate for Armor Coat

1. Mineral Aggregate for Armor Coat.....Page 7-1

DATE: 08-23-00
REVISED: 02-12-04

| Minimum Material Certificate, Sample and Inspection Requirements | | | | | | | |
|--|---------------------|---|---|------------|--|------------------------------------|----------|
| MATERIAL | TYPE OF TEST | Q.C. SAMPLING AND TESTING BY CONTRACTOR | VERIFICATION SAMPLING AND TESTING BY NDOR | | | LOCATION OF ADDITIONAL INFORMATION | |
| SECTION: 7 – Mineral Aggregate for Armor Coat | | | FIELD PERSONNEL | BRANCH LAB | LINCOLN LAB | NOTE No. | PAGE No. |
| 1) Mineral Aggregate for Armor Coat | Quality & Gradation | ----- | <p>See Standard Specifications, Supplemental Specifications, and/or the Project Special Provisions for Mineral Aggregate for Armor Coat sampling and testing requirements.</p> <p>Project personnel will provide the 10 and 60 pound samples needed to perform the testing shown under the Lincoln Lab column.</p> <p>The sample shall be taken at the project.</p> | ----- | <p>One 60 pound sample for quality tests first 1,000 cubic yards. If so designated on the DR FORM 324 "Source of Aggregates to Be Used".</p> <p>One 10 pound sample for gradation tests each 1000 cubic yard or fraction thereof. (Duplicate of sample tested in the field).</p> | 4 | 4 |