Materials Sampling Guide

Table of Contents

Section 8

Crushed Rock and Crushed Rock Screenings for Base Course

1.	Crushed Rock for Base Course	Page 8-1
2.	Crushed Rock Screenings for Base Course	Page 8-1

DATE: 08-23-00 REVISED: 04-09-04

		Minimum Material Certificate, Sample and Inspection Requirements					
MATERIAL	TYPE OF TEST	Q.C. SAMPLING AND TESTING BY CONTRACTOR	VERIFICATION SAMPLING AND TESTING BY NDOR			LOCATION OF ADDITIONAL INFORMATION	
Section: 8 – Base Course		k and Crushed Rock Screenings for	FIELD PERSONNEL	BRANCH LAB	LINCOLN LAB	NOTE No.	PAGE No.
 Crushed Rock for Base Course Crushed Rock Screenings for Base Course 	Quality, Gradation & Compaction		One sample for gradation testing, each 1000 cubic yards or fraction thereof. Additional samples should be taken at the discretion of the Project Manager to confirm his judgement that segregation, degradation or contamination of the material has not occurred prior to incorporation in to the work. Project personnel will supply the 60 pound sample needed to perform the testing shown under the Lincoln Lab column. The samples shall be taken at the project.		One 60 pound sample for quality and gradation tests each 3000 cubic yards or fraction thereof. This will be a duplicate of sample tested in the field. One 60 pound sample for moisture density curve if required. This sample shall be submitted prior to placement.	5	4