

Fly Ash

These brands of Type C or F fly ash are accepted for use with a manufacturer certification. This fly ash should be sampled only when,

- a. requested by the Materials and Research Division,
- b. if the inspector questions the material,
- c. if it has been in storage for 90 days or more.

(Section 1008)

Updated on 1-16-04

PRODUCT	POWER PLANT & LOCATION	TYPE	PLANT CODES	AVE. SPECIFIC GRAVITY
Boral Material Technologies	Laramie River Station Wheatland, WY	C	BL	2.60
	Plant Monticello Monticello, TX	F	BM	2.40
Flatwater Materials	Hastings Power Plant Hastings, NE	C	FH	2.55
	Grand Island Station Grand Island, NE	C	GI	2.55
LaFarge North America	Owensboro Municipal Utility Lockport, IL	F	LO	2.50
Plains Pozzolanic	Gerald Gentleman Station-Unit 1 Sutherland, NE	C	S1	2.65
	Gerald Gentleman Station-Unit 2 Sutherland, NE	C	S2	2.65
ISG	Coal Creek Plant Underwood, ND	F	CC	2.20
	Council Bluffs Station Council Bluffs, IA	C	CB	2.60
	Port Neal 3 Sioux City, IA	C	P3	2.70
	Port Neal 4 Sioux City, IA	C	P4	2.60
	Tatum Plant Tatum, TX	F	IT	2.55
Nebraska Ash Co.	O.P.P.D. North Omaha Station Omaha, NE	C	NO	2.45
	O.P.P.D. Nebraska Ash Nebraska City, NE	C	NC	2.50
	Escalante Generating Station Escalante, NM	F	NE	2.10
	San Juan Generating Station Waterflow, NM	F	NS	2.00