

## SECTION 915 -- GRANULAR SUBDRAINS

### 915.01 -- Description

The Contractor shall construct granular subdrains as prescribed in the plans.

### 915.02 -- Material Requirements

Aggregate that is used in granular subdrains shall conform to any of the gradation requirements for Concrete Fine Aggregate in Section 1033, Table 1033.02A.

### 915.03 -- Construction Methods

1. The Contractor shall excavate subdrain trenches to the dimensions and the elevations shown in the plans.
2. a. The Contractor shall provide and place aggregate in the trench as prescribed in the plans.  
b. The aggregate shall be fine aggregate for concrete as prescribed in Table 1033.02A.
3. After the aggregate has been placed, the trench shall be backfilled to the shoulder surface.
4. All backfill material shall be compacted to a density equal to the density of the adjacent shoulder.
5. Surplus material shall be disposed of on adjacent slopes.

### 915.04 -- Method of Measurement

The "Granular Subdrain" shall be measured by the each.

### 915.05 -- Basis of Payment

- |    |                               |                 |
|----|-------------------------------|-----------------|
| 1. | <u>Pay Item</u>               | <u>Pay Unit</u> |
|    | Granular Subdrain, Type _____ | Each (ea)       |
|    | Granular Subdrain             | Each (ea)       |
2. Payment is full compensation for all work prescribed in this Section.