

SECTION 903 -- REMOVE AND RESET GUARDRAIL

903.01 -- Description

1. Removing guardrail shall include the removal of all cable, approach sections, terminal sections, anchorage sections, and beam guardrail materials, fittings, and posts from locations shown in the plans or designated by the Engineer. Concrete anchors shall be removed in their entirety and disposed of by the Contractor.

2. Resetting guardrail shall include setting guardrail salvaged from the project or furnished and delivered to the project by others as indicated in the plans. New concrete anchors shall be furnished by the Contractor. The Contractor shall furnish all new posts, offset blocks, hardware, and incidentals required to install the salvaged rail elements.

903.02 -- Material Requirement

New materials, replacement materials, and concrete shall conform to the requirements of Section 902.

903.03 -- Construction Methods

1. a. The Contractor shall remove guardrail so that all materials may be salvaged.

b. Cable removed and not to be reset shall be rolled on spools, and the length of cable on each spool shall not exceed 600 meters.

c. (1) Salvaged materials shall be stored on or near the right-of-way at locations designated by the Engineer.

(2) Hardware shall be placed in suitable containers.

(3) No more than 25 kg of salvaged material shall be placed in a single container.

d. If the plans call for "Resetting Guardrail", the Contractor removing the existing guardrail shall replace all materials damaged during removal at no additional cost to the Department.

2. The Contractor shall reset the guardrail at the locations shown in the plans or as directed by the Engineer. The work shall be done in accordance with the requirements of Section 902.

3. End posts may be reset providing the 200 mm x 200 mm x 6 mm plate is removed from the bottom of the post and a support bracket is installed on the post at the ground line.

4. Extra line posts may be converted to end posts by removing hook bolts and installing an end post cap and a support bracket as shown in the plans.

903.04 -- Method of Measurement

1. Resetting cable and "W" and "thrie"-beam guardrail is measured by the meter. The Department will compute the length of guardrail reset by the meter from center to center of guardrail element end connections, including approach and terminal sections, for each continuous length of guardrail.

2. Removal of cable and "W" and "thrie"-beam guardrails is measured by the meter. The Department will compute the length of guardrail removed by the meter from center to center of guardrail element end connections, including approach and terminal sections, for each continuous length of guardrail.

903.05 -- Basis of Payment

- | 1. | <u>Pay Item</u> | <u>Pay Unit</u> |
|----|------------------|-----------------|
| | Reset Guardrail | Meter (m) |
| | Remove Guardrail | Meter (m) |
2. Payment is full compensation for all work required in this Section.